

BIJLAGENBLAD INNODEMPEL

Geluidvermogeniveau in octaafbanden van de toevoer/uitblaas lucht

Geluidvermogeniveau $L_w = L_{WA} + K_w$

Tabel K_w

Type	Hz							
	63	125	250	500	1K	2K	4K	8K
Inno-100-RP	6	4	3	0	-9	-10	-17	-24
Inno-125-RP	4	2	1	0	-8	-10	-18	-24
Inno-160-RP	5	4	3	0	-9	-10	-18	-22
Inno-200-RP	4	2	5	-4	-10	-15	-20	-25
Inno-250-RP	6	6	8	4	-7	-7	-15	-20
Inno-315-RP	6	8	9	0	-6	-7	-17	-20

Tussenschakeldemping van type Inno-RP

De tussenschakeldemping zonder eindreflectie.

ISO 7235:2003

Tabel ΔL (dB)

Aantal openingen	Hz							
	63	125	250	500	1K	2K	4K	8K
Inno-100-RP,1	6.5	7.0	4.0	9.5	13	16	18	22
Inno-100-RP,3	3.0	3.5	2.5	5.5	8.5	8.5	15	19
Inno-100-RP,5	1.5	2.5	1.5	3.5	6.0	6.5	12	17
Inno-125-RP,2	5.0	6.0	5.0	5.0	12	13	19	21
Inno-125-RP,5	2.0	2.0	2.5	3.0	8.5	8.0	14	19
Inno-125-RP,8	1.0	1.5	1.5	2.5	6.0	5.0	11	18
Inno-160-RP,1	6.5	7.0	4.0	9.5	13	16	18	22
Inno-160-RP,3	3.0	3.5	2.5	5.5	8.5	8.5	15	20
Inno-160-RP,5	1.5	2.5	1.5	3.5	6.0	6.0	12	17
Inno-200-RP,2	4.0	6.5	2.5	5.5	13	14	18	16
Inno-200-RP,5	2.0	3.0	1.5	2.5	9.5	8.5	14	15
Inno-200-RP,8	2.0	2.0	1.0	1.5	7.0	7.0	13	14
Inno-250-RP,0	5.0	4.0	3.0	7.0	13	18	18	17
Inno-250-RP,3	4.0	4.0	2.0	6.0	11	16	16	15
Inno-250-RP,6	3.0	2.0	2.0	5.0	9.0	13	15	15
Inno-250-RP,10	2.0	2.0	1.0	3.0	7.0	11	14	13
Inno-315-RP,0	5.0	5.0	3.0	6.0	12	15	16	18
Inno-315-RP,4	4.0	4.0	3.0	4.0	10	14	14	16
Inno-315-RP,8	3.0	3.0	2.0	3.0	8.0	12	13	15
Inno-315-RP,14	2.0	1.0	1.0	2.0	7.0	8.0	10	13



MERFORD
NOISE CONTROL

AKOESTISCHE MATERIALEN - GELUIDDEMPERS