

MKD-200

Stauf MKD-200 glue is a water-based adhesive paste with strong adhesive powers.

Solvent-free MKD-200 glue is odourless and does not contain any harmful substances. The adhesive paste is specifically intended for gluing acoustic materials on brick, plaster, wood and concrete surfaces.



Applications

Stauf MKD-200 is intended specifically for gluing acoustic materials such as Flamex, Akotherm, Soundstone, polyurethane foam and mineral wool to walls and ceilings made of concrete, brick, plaster and wood. The adhesive paste has strong adhesive powers, rendering result sealing unnecessary.

Weight

3.5 kg bucket

Shape, appearance and colour

White adhesive paste, packaged in 3.5 kg buckets

Composition

Odourless, solvent-free, water-based adhesive paste.

Other technical information

Initial adhesive powers: > 20 g/cm².

Resistance

Age-resistant.

Installation

- At least one of the surfaces to be glued must be open-celled or porous.
- Dry the surface and remove dust and grease beforehand. Concrete must be free of discharge fluid, formwork oil, etc.

- Apply dots or beads of glue or apply glue using a serrated spatula across the whole surface of one side. Less glue is needed for 'rigid' sheets (such as Soundstone) than for 'pliant' sheets
- Within 15 minutes press the glued area onto the surface (apply a lot of pressure!). The material to be glued should now remain in place immediately, including the material above your head. Should this not be the case, more glue should be applied.
- Processing temperature: at least + 5 °C, but processing works better at temperatures above 15 °C
- Use: 0,5 - 1 kg/m² if using the glue on one side, depending on the material to be glued and the roughness of the surface.
- Drying time: approximately 24 hours, depending on temperature and humidity.
- Storage and transport: must definitely be cool and frost-proof
- Storage life: one year.
- We advise you to test the glue in advance.

Disclaimer

The recommendations and information listed in this product sheet are shown as complete and accurate as possible, but offer no guarantees. Check with one of our specialists or perform your own test.

MKD-200

Solvent-free, water-based, odourless adhesive paste

PROPERTIES

- Solvent-free
- High initial adhesive powers
- Odourless

APPLICATIONS

For gluing acoustic materials such as Flamex, Akotherm, Soundstone, polyurethane foam and mineral wool to walls and ceilings made of concrete, brick, plaster and wood.



MERFORD
NOISE CONTROL

ACOUSTIC MATERIALS - ADHESIVES